

EAN : 542503 853125 1
SKU : SXAE00026

- Charge & maintenance functions
- Automatic management by microprocessor
- Maximum current 8 Amp
- Suitable for 12V batteries
- Automatic voltage selection
- Up to 9 steps intelligent charging cycles
- No battery removal required
- For all types of lead-acid batteries
- Supplied with clamps



SPECIFICATIONS

INPUT	Voltage	220 - 240 Volt AC 50 - 60Hz	
	Plug	EU	Type Standard
OUTPUT	Nominal Voltage	12V	Max Output 8A
	Cable length	1,5m + 0,5m clamps cable	
	Terminals	Clamps	
CAPACITY	Charge	5 - 160 Ah	Maintain 5 - 250 Ah
	Recovery	YES - specific recondition mode	
	Power Supply	YES - 13,8V - 5A MAX 80 Watt	
	Compatibility	Lead Acid battery : AGM , GEL, VLRA, WET, LIQUID	
INTERFACE	LCD Display	Charging status - Error Indicator	
	MMI	5 selection modes: slow/fast - battery type (STD/AGM) - recond - power supply	
IP CLASSIFICATION	IP 65		
CERTIFICATION	CE EN60335 - 2 - 29 - LVD - EMC - RoHS		

SKU	EAN code	5425038 53125 1			
	Length	192mm	Width	72mm	Height 308mm
	Gross weight	1.240gr	Net weight	960gr	
Carton box	EAN code	2 5425038 53125 5			
	Length	633mm	Width	249mm	Height 212mm
	Gross weight	7,70kg	Net weight	5,76kg	
	Qte of SKUs per carton box	6			
PALLET	EAN code	4 5425038 53125 9			
	Length	120cm	Width	80cm	Height 142cm
	Gross weight	252kg	Net weight	173kg	
	Carton per layer	5	Qte of layers	6	Cartons per pallet 30
	Qty SKUs per pallet	180			
	type of pallet	Plywood pallet			